

FORM PTO-1390  
(REV. 9-2001)

U.S. DEPARTMENT OF COMMERCE PATENT AND TRADEMARK OFFICE

ATTORNEY'S DOCKET NUMBER

TRANSMITTAL LETTER TO THE UNITED STATES  
DESIGNATED/ELECTED OFFICE (DO/EO/US)  
CONCERNING A FILING UNDER 35 U.S.C. 371

915-418

U.S. APPLICATION NO. (If known, see 37 CFR 1.5)

10/019745

INTERNATIONAL APPLICATION NO.

PCT/IB00/00989

INTERNATIONAL FILING DATE

30 June 2000

PRIORITY DATE CLAIMED

30 June 1999

TITLE OF INVENTION

Service Management

APPLICANT(S) FOR DO/EO/US


Kalle Ahmavaara

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This is an express request to begin national examination procedures (35 U.S.C. 371(f)). The submission must include items (5), (6), (9) and (21) indicated below.
4. ☐ The US has been elected by the expiration of 19 months from the priority date (Article 31).
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
  - a. ☐ is attached hereto (required only if not communicated by the International Bureau).
  - b. ☒ has been communicated by the International Bureau.
  - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☐ An English language translation of the International Application as filed (35 U.S.C. 371(c)(2)).
  - a. ☐ is attached hereto.
  - b. ☐ has been previously submitted under 35 U.S.C. 154(d)(4).
7. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
  - a. ☐ are attached hereto (required only if not communicated by the International Bureau).
  - b. ☐ have been communicated by the International Bureau.
  - c. ☐ have not been made; however, the time limit for making such amendments has NOT expired.
  - d. ☐ have not been made and will not be made.
8. ☐ An English language translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371 (c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ An English language translation of the annexes of the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

## Items 11 to 20 below concern document(s) or information included:

11. ☒ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☒ A **FIRST** preliminary amendment.
14. ☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
15. ☐ A substitute specification.
16. ☐ A change of power of attorney and/or address letter.
17. ☐ A computer-readable form of the sequence listing in accordance with PCT Rule 13ter.2 and 35 U.S.C. 1.821 - 1.825.
18. ☒ A second copy of the published international application under 35 U.S.C. 154(d)(4).
19. ☐ A second copy of the English language translation of the international application under 35 U.S.C. 154(d)(4).
20. ☒ Other items or information: copy Int'l Preliminary Examination Report

U.S. APPLICATION NO. <b>10/019745</b> INTERNATIONAL APPLICATION NO. <b>PCT/IB00/00989</b>		ATTORNEY'S DOCKET NUMBER <b>915-418</b>	
21. <input checked="" type="checkbox"/> The following fees are submitted: <b>BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)):</b> Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO and International Search Report not prepared by the EPO or JPO. .... <b>\$1040.00</b>  International preliminary examination fee (37 CFR 1.482) not paid to USPTO but International Search Report prepared by the EPO or JPO ..... <b>\$890.00</b>  International preliminary examination fee (37 CFR 1.482) not paid to USPTO but international search fee (37 CFR 1.445(a)(2)) paid to USPTO ..... <b>\$740.00</b>  International preliminary examination fee (37 CFR 1.482) paid to USPTO but all claims did not satisfy provisions of PCT Article 33(1)-(4) ..... <b>\$710.00</b>  International preliminary examination fee (37 CFR 1.482) paid to USPTO and all claims satisfied provisions of PCT Article 33(1)-(4) ..... <b>\$100.00</b>  <b>ENTER APPROPRIATE BASIC FEE AMOUNT =</b>		<b>CALCULATIONS PTO USE ONLY</b>          <div style="display: flex; justify-content: space-between;"> <span>\$</span> <span><b>890.00</b></span> </div>	
Surcharge of <b>\$130.00</b> for furnishing the oath or declaration later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(e)).		<div style="display: flex; justify-content: space-between;"> <span>\$</span> <span></span> </div>	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	<b>29</b> - 20 =	<b>9</b>	x <b>\$18.00</b>
Independent claims	<b>2</b> - 3 =	<b>-0-</b>	x <b>\$84.00</b>
MULTIPLE DEPENDENT CLAIM(S) (if applicable)		+ <b>\$280.00</b>	
<b>TOTAL OF ABOVE CALCULATIONS =</b>			\$ <b>1,052.00</b>
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27. The fees indicated above are reduced by 1/2.			\$
<b>SUBTOTAL =</b>			\$ <b>1,052.00</b>
Processing fee of <b>\$130.00</b> for furnishing the English translation later than <input type="checkbox"/> 20 <input type="checkbox"/> 30 months from the earliest claimed priority date (37 CFR 1.492(f)).			\$
<b>TOTAL NATIONAL FEE =</b>			\$ <b>1,052.00</b>
Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). <b>\$40.00</b> per property +			\$
<b>TOTAL FEES ENCLOSED =</b>			\$ <b>1,052.00</b>
			Amount to be refunded: \$
			charged: \$
a. <input checked="" type="checkbox"/> A check in the amount of \$ <u><b>1,052.00</b></u> to cover the above fees is enclosed.  b. <input type="checkbox"/> Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees. A duplicate copy of this sheet is enclosed.  c. <input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account No. <u><b>23-0442</b></u> . A duplicate copy of this sheet is enclosed.  d. <input type="checkbox"/> Fees are to be charged to a credit card. <b>WARNING:</b> Information on this form may become public. <b>Credit card          information should not be included on this form.</b> Provide credit card information and authorization on PTO-2038.			
<b>NOTE:</b> Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137 (a) or (b)) must be filed and granted to restore the application to pending status.			
SEND ALL CORRESPONDENCE TO: Francis J. Maguire WARE, FRESSOLA, VAN DER SLUYS & ADOLPHSON LLP 755 Main Street, PO Box 224 Monroe CT 06468		 SIGNATURE  Francis J. Maguire NAME  <u>31,391</u> REGISTRATION NUMBER	

915-418

IN THE U.S. PATENT AND TRADEMARK OFFICE

Re application of :

K. Ahmavaara :

Filed: Herewith :

For: SERVICE MANAGEMENT

Claiming priority from:

International Application PCT/IB00/00989

Filed: June 30, 2000

PRELIMINARY AMENDMENT A

Assistant Commissioner for Patents  
U.S. Patent and Trademark Office  
Washington DC 20231

Sir:

Please preliminarily amend the above-referenced application  
as follows:

FILING OF PAPERS AND FEES BY "EXPRESS MAIL"  
WITH CERTIFICATE IN ACCORDANCE WITH 37 CFR 1.10

I hereby certify that this correspondence is being  
deposited with the United States Postal Service on the  
date shown below with sufficient postage as "Express Mail"  
in an envelope with Mailing Label No. EV 005523857 US  
placed thereon prior to mailing and addressed to the  
Assistant Commissioner for Patents, Washington DC 20231.

Judith Schick

Dated:

*Judith Schick*  
12-28-01

IN THE SPECIFICATION:

At page 1, after line 1, please insert new headings as follows:

--BACKGROUND OF THE INVENTION

1. Technical Field--; and

prior to line 6, please insert a new heading as follows:

--2. Discussion of Related Art--.

At page 3, prior to line 1, please insert a new heading as follows:

--DISCLOSURE OF INVENTION--.

At page 7, prior to line 5, please insert a new heading as follows:

--BRIEF DESCRIPTION OF THE DRAWING--; and

prior to line 13, please insert a new heading as follows:

--BEST MODE FOR CARRYING OUT THE INVENTION--.

IN THE CLAIMS:

Please cancel claims 30, 31 and 32.

The remaining claims have been amended as follows:

1. (Amended) A method of establishing a connection in a telecommunications system in which an intermediate network provides for communications between a user terminal and one or more of a plurality of serving network entities each capable of providing communications services to the user terminal by means of at least one telecommunications protocol, the method comprising the steps of the intermediate network transmitting to the user terminal an indication of the communications services

provided by each one of the serving network entities and the user terminal selecting one or more of the communication services.

4. (Amended) A method as claimed in claim 1 wherein the user terminal is capable of communicating by radio with the intermediate network.

5. (Amended) A method as claimed in claim 1 wherein the intermediate network is operable according to the Universal Mobile Telecommunications System or a derivative thereof.

7. (Amended) A method as claimed in claim 1, wherein the intermediate network is a radio access network.

9. (Amended) A method as claimed in claim 1, wherein said indication is transmitted to the user terminal during the establishment of a connection between the user terminal and the intermediate network.

10. (Amended) A method as claimed in claim 1, wherein said indication is transmitted to the user terminal during establishment of a radio resource control connection between the user terminal and the intermediate network.

11. (Amended) A method as claimed in claim 1, wherein said indication is transmitted to the user after establishment of the connection between the user terminal and the intermediate network.

12. (Amended) A method as claimed in claim 1, wherein said indication is transmitted to the user terminal during a procedure of the intermediate network consequent on reallocation of

equipment in the intermediate network serving the connection with the user terminal.

13. (Amended) A method as claimed in claim 11, wherein said indication is transmitted to the user terminal in consequence of a serving radio network controller relocation.

14. (Amended) A method as claimed in claim 1, wherein said indication is transmitted to the user terminal in consequence of a change in serving network entity.

15. (Amended) A method as claimed in claim 1, wherein the intermediate network is capable of adjusting a number of paging areas according to a number of serving network entities.

16. (Amended) A method as claimed in claim 1, wherein at least one of the serving network entities is capable of providing for communications between the terminal and another telecommunications network.

17. (Amended) A method as claimed in claim 1, wherein at least one of the serving network entities is capable of providing for circuit switched communications between the terminal and another telecommunications network.

18. (Amended) A method as claimed in claim 1, wherein at least one of the serving network entities is capable of providing for packet switched communications between the terminal and another telecommunications network.

19. (Amended) A method as claimed in claim 1, wherein the intermediate network is capable of routing signals between the user terminal and one of the serving network entities.

21. (Amended) A method as claimed in claim 19, wherein the intermediate network includes a Universal Mobile Telecommunications System radio network controller capable of performing said routing.

22. (Amended) A method as claimed in claim 1, comprising establishing for each user terminal for each serving network entity with which that terminal is registered an instance of a management process for informing a respective serving network entity of changes in a connection path to a respective mobile station through the intermediate network, whereby on a change in the connection path to the mobile station through the intermediate network, each serving network entity is informed of the change by means of the respective instance.

25. (Amended) A method as claimed in claim 23, comprising the step of, in consequence of said indication of serving network entities and the communications services provided by each one, modifying an instance of the management process for informing a respective serving network entity of changes in the connection path to said mobile station through the intermediate network.

26. (Amended) A method as claimed in claim 22, wherein the management process is a mobility management process.

28. (Amended) A telecommunications system comprising:  
a user terminal;  
one or more serving network entities each capable of providing communications services to the user terminal by means of at least one respective telecommunications protocol; and  
an intermediate network providing for communications between the user terminal and one or more of the serving network entities, and capable of transmitting to the user terminal an


entities, and capable of transmitting to the user terminal an indication of the serving network entities and the communications services provided by each one.

29. (Amended) A telecommunications system as claimed in claim 28, comprising processing apparatus capable of for each user terminal establishing for each serving network entity with which that terminal is registered an instance of a management process for informing a respective serving network of changes in a connection path to a respective user terminal through the intermediate network, whereby on a change in the connection path to the user terminal through the intermediate network, each serving network entity is informed of the change by means of the respective instance.

REMARKS

This preliminary amendment is submitted for the purpose of placing the application into standard U.S. format and to eliminate multiple dependencies of the claims. Approval and allowance are requested.

Respectfully submitted,



Francis J. Maguire  
Attorney for the Applicant  
Registration No. 31,391

FJM/mbh  
December 28, 2001  
WARE, FRESSOLA, VAN DER SLUYS  
& ADOLPHSON LLP  
755 Main Street, PO Box 224  
Monroe CT 06468  
(203) 261-1234



Version with Markings to Show Changes Made

Claims 30-32 have been cancelled.

The following claims have been amended:

1. (Amended) A method of establishing a connection in a telecommunications system in which an intermediate network provides for communications between a user terminal and one or more of a plurality of serving network entities each capable of providing communications services to the user terminal by means of at least one telecommunications protocol, the method comprising the [step] steps of the intermediate network transmitting to the user terminal an indication of [the serving network entities and] the communications services provided by each one of the serving network entities and the user terminal selecting one or more of the communication services.

4. (Amended) A method as claimed in [any preceding] claim 1 wherein the user terminal is capable of communicating by radio with the intermediate network.

5. (Amended) A method as claimed in [any preceding] claim 1 wherein the intermediate network is operable according to the Universal Mobile Telecommunications System or a derivative thereof.

7. (Amended) A method as claimed in [any preceding] claim 1, wherein the intermediate network is a radio access network.

9. (Amended) A method as claimed in [any preceding] claim 1, wherein [the] said indication is transmitted to the user

terminal during the establishment of a connection between the user terminal and the intermediate network.

10. (Amended) A method as claimed in [any preceding] claim 1, wherein [the] said indication is transmitted to the user terminal during establishment of a radio resource control connection between the user terminal and the intermediate network.

11. (Amended) A method as claimed in [any of claims 1 to 8] claim 1, wherein said indication is transmitted to the user after establishment [by] of the [of a] connection between the user terminal and the intermediate network.

12. (Amended) A method as claimed in [any of claims 1 to 8 or 11] claim 1, wherein [the] said indication is transmitted to the user terminal during a procedure of the intermediate network consequent on reallocation of equipment in the intermediate network serving the connection with the user terminal.

13. (Amended) A method as claimed in claim 11 [as dependant directly or indirectly on claim 5], wherein [the] said indication is transmitted to the user terminal in consequence of a serving radio network controller relocation.

14. (Amended) A method as claimed in [any preceding] claim 1, wherein [the] said indication is transmitted to the user terminal in consequence of a change in serving network entity.

15. (Amended) A method as claimed in [any preceding] claim 1, wherein the intermediate network is capable of adjusting [the] a number of paging areas according to [the] a number of serving network entities.

16. (Amended) A method as claimed in [any preceding] claim 1, wherein at least one of the serving network entities is capable of providing for communications between the terminal and another telecommunications network.

17. (Amended) A method as claimed in [any preceding] claim 1, wherein at least one of the serving network entities is capable of providing for circuit switched communications between the terminal and another telecommunications network.

18. (Amended) A method as claimed in [any preceding] claim 1, wherein at least one of the serving network entities is capable of providing for packet switched communications between the terminal and another telecommunications network.

19. (Amended) A method as claimed in [any preceding] claim 1, wherein the intermediate network is capable of routing signals between the user terminal and one of the serving network entities.

21. (Amended) A method as claimed in claim 19 [or 20], wherein the intermediate network includes a Universal Mobile Telecommunications System radio network controller capable of performing [the] said routing.

22. (Amended) A method as claimed in [any preceding] claim 1, comprising establishing for each user terminal for each serving network entity with which that terminal is registered an instance of a management process for informing [the] a respective serving network entity of changes in [the] a connection path to [the] a respective mobile station through the intermediate network, whereby on a change in the connection path to the mobile station through the intermediate network, each serving network

entity [may be] is informed of the change by means of the respective instance.

25. (Amended) A method as claimed in claim 23 [or 24], comprising the step of, in consequence of [the] said indication of serving network entities and the communications services provided by each one, modifying an instance of the management process for informing a respective serving network entity of changes in the connection path to [a the] said mobile station through the intermediate network.

26. (Amended) A method as claimed in [any of claims 22 to 25] claim 22, wherein the management process is a mobility management process.

28. (Amended) A telecommunications system comprising:  
a user terminal;  
one or more serving network entities each capable of providing communications services to the user terminal by means of at least one respective telecommunications protocol; and  
an intermediate network providing for communications between [a] the user terminal and one or more of the serving network entities, and [being] capable of transmitting to the user terminal an indication of the serving network entities and the communications services provided by each one.

29. (Amended) A telecommunications system as claimed in claim 28, comprising processing apparatus capable of for each user terminal establishing for each serving network entity with which that terminal is registered an instance of a management process for informing [the] a respective serving network of changes in [the] a connection path to [the] a respective user terminal through the intermediate network, whereby on a change in

the connection path to the user terminal through the intermediate network, each serving network entity [may be] is informed of the change by means of the respective instance.

## SERVICE MANAGEMENT

This invention relates to managing services and overseeing mobility of a user in a telecommunication network. The invention is especially, but not exclusively, suitable for implementation in the proposed UMTS (Universal Mobile Telecommunications System) architecture.

Figure 1 shows generally the architecture proposed for UMTS. A mobile station (MS) 1 can communicate by radio with one or more base stations (BS) 2. Each base station is linked by an Iub interface 3 to a single radio network controller (RNC) 4. Each RNC can be linked to one or more BSs. An RNC can be linked to another RNC by an Iur interface 5. Each RNC is linked by an Iu interface 6 to a core network (CN) 7. The CN includes one or more serving nodes that can provide communication services to a connected mobile station, for example a mobile switching centre (MSC) or a serving GPRS (general packet radio service) support node (SGSN) 8. These units are connected by the Iu interface to the RNCs. The CN is also connected to other telecommunications networks 9 such as fixed line networks or other mobile networks to allow onward connection of communications outside the UMTS network. The CN also includes other units such as a home location register (HLR) 10 and a visitor location register (VLR) 11 which help to control access to the network. The BSs and the RNCs and their interconnections constitute a UMTS terrestrial radio access network (UTRAN).

A mobile station can communicate with a core network via an RNC and a base station connected to that RNC. In soft handover (macrodiversity), the mobile station can send traffic communications via more than one base station. Those base stations may be connected to the same RNC or to different RNCs. If the base stations are connected to different RNCs then those RNCs communicate directly with each other via the Iur interface to co-ordinate their actions and to combine signals received from the mobile station. One of those RNCs is designated as the serving

RNC and the others as drift RNCs. Communications between the user and the core network go via the serving RNC only. Thus, whether the mobile station is in soft handover or not its connection to the CN is through a single RNC. It can also arise in other circumstances than macrodiversity that a BS is controlled by a drift RNC, with communications going via serving a serving RNC to the core network.

In the core network each serving node such as an MSC or SGSN can provide a set of services to the mobile station. For example:

- An MSC can provide circuit switched (CS) communications, for example for speech, fax or non-transparent data services, and therefore has a link to other entities in the circuit switched domain such as other CS mobile networks such as GSM (Global System for Mobile Communications) and CS fixed wire networks such as conventional voice telephony networks.
- An SGSN can provide packet switched (PS) communications, for example for packet data protocol (PDP) contexts for internet protocol (IP) data transmission, and therefore has a link to other entities in the packet switched domain such as GPRS-equipped GSM networks and the internet.

The division of services between serving nodes is specified in the system specification and is strictly tied to the assumed network architecture. There may be other nodes than the MSC or SGSN providing overlapping or additional services.

It can be envisaged that in the future some services may be provided differently from the current arrangement. For example, speech services seem likely to migrate from the CS to the PS domain. In order to implement these changes to the network in the form described above is likely to cause substantial disruption. For example, to shift the provision of a fundamental service such as voice traffic to the PS domain may require routing hardware and software, as well as software in each mobile station, to be updated. This would cause great expense and inconvenience to network operators.

It would be desirable for there to be a way in which an operator can move a service previously executed by one type of network node to another type of network node with less disruption, or to introduce a new service via a new or an existing core network .

According to one aspect of the present invention there is provided a method of establishing a connection in a telecommunications system in which an intermediate network provides for communications between a user terminal and one or more of a plurality of serving network entities each capable of providing communications services to the user terminal by means of at least one telecommunications protocol, the method comprising the step of the intermediate network transmitting to the user terminal an indication of the serving network entities and the communications services provided by each one.

According to a second aspect of the present invention there is provided a telecommunications system comprising: a user terminal; a plurality of serving network entities each capable of providing communications services to the user terminal by means of at least one respective telecommunications protocol; an intermediate network providing for communications between a user terminal and one or more of the serving network entities, and being capable of transmitting to the user terminal an indication of the serving network entities and the communications services provided by each one.

Suitably, the user terminal selects the set of serving network entities which together support the set of services the user terminal wishes to use, and attaches to the serving network entities of the set.

Suitably the said indication is generated by the intermediate network. For this purpose the intermediate network may suitably store information defining the



available serving network entities and the service(s) capable of being provided by each one, preferably together with an identifier for each network entity.

The said indication may be transmitted to the user terminal during and/or after establishment by the user terminal of a connection with the intermediate network. In the latter case, the indication may suitably be transmitted in response to a mobility event of the mobile terminal, for example during or generally in consequence of a procedure of the intermediate network consequent on reallocation of equipment in the intermediate network serving the connection with the user terminal. That event may be a serving radio network controller relocation in, for example, a UMTS system or the like.

The intermediate network is suitably capable of adjusting the number of paging areas according to the number of serving network entities, for example with one paging area for each serving network entity. Alternatively, all, or at least more than one, of the serving network entities may use a common paging area.

The intermediate network is suitably capable of constituting a communication path between the user terminal and one or more of the network entities. The user terminal and one or more of the network entities are preferably capable of communicating via the intermediate network.

There may be a plurality of mobile stations, which are preferably operable in similar manner, whereby each mobile station can individually establish or register for communications with one or more serving network entities.

Suitably, for the user terminal an instance of a management process is established for each serving network entity with which that terminal is registered for informing the respective serving network of changes in the connection path to the respective terminal through the intermediate network. The said instance may be run on

processing apparatus local to the user terminal. On a change in the connection path to the mobile station through the intermediate network, each serving network entity may be informed of the change by means of the respective instance.

Suitably the intermediate network is capable of transmitting to a mobile station an indication of one or a plurality of serving network entities and the communications services provided by each one. Preferably, in order to receive a desired service a mobile station is capable of determining one of the serving network entities indicated as providing that service and attempting to establish a connection with that serving network entity via the intermediate network. Preferably, in consequence of the said indication of serving network entities and the communications services provided by each one, the system (most preferably the terminal) is capable of establishing a further instance of the management process for informing a respective serving network entity of changes in the connection path to a the said mobile station through the intermediate network. Alternatively, when a list of services is communicated to a terminal the terminal may already know which services are related to which serving nodes and consecutive to which management process. In that case if later the terminal needs to initialise a communication for a specific service then it may already be aware of which serving node it should contact, and thus suitably of which management process a request for such initialisation may be related to. In consequence of the said indication of serving network entities and the communications services provided by each one the system may suitably be capable of terminating an instance of the management process for informing a respective serving network entity of changes in the connection path to the said mobile station through the intermediate network.

The management process may be a mobility management process, suitably operable in accordance with a mobility management protocol, suitably a mobility management protocol of or for the Universal Mobile Telecommunications System or a derivative thereof.

The service(s) related to such management processes may, for example, be call control entities, session management entities, PDP (packet data protocol) entities, SMS (short message service) handling entities, voice-over-IP (internet protocol) entities, H.323 or H.324 entities, or supplementary service instances.

Some preferred features of all aspects of the invention will now be set out.

Suitably the user terminal is capable of communicating by radio and/or another medium with the intermediate network. The user terminal may be a unit that can be termed a mobile station, whether it is in fact mobile or immobile. The user terminal may be a mobile telephone.

The intermediate network is suitably operable according to the Universal Mobile Telecommunications System or a derivative thereof.

The intermediate network may be a radio access network, and is preferably a Universal Mobile Telecommunications System radio access network. The intermediate network is suitably capable of routing signals between the user terminal and one of the serving network entities, for example on the basis of (or in dependence on) a core network domain indicator. The intermediate network may include a Universal Mobile Telecommunications System radio network controller capable of performing the said routing.

Suitably at least one of the serving network entities is capable of providing for communications between the intermediate network and another telecommunications network. Each serving network entity may be a core network. Each serving network entity may include a home location register and/or a visitor location register. Suitably one or more of the serving network entities is capable of providing for circuit switched communications between the intermediate network and another telecommunications network. Suitably one or more of the serving network entities is capable of providing

for packet switched communications between the intermediate network and another telecommunications network.

The or each serving network entity may suitably but not necessarily be a serving network domain or serving network element.

The present invention will now be described by way of example with reference to the accompanying drawings, in which:

figure 1 is a schematic diagram of the currently-proposed architecture for a UMTS telecommunications system;

figure 2 is a schematic diagram of a modified architecture for a UMTS telecommunications system; and

figure 3 is a flow diagram illustrating the operation of a method in the system of figure 2.

The network shown in figure 2 is arranged so that instead of services being offered to a mobile station by a set of rigidly configured core network nodes, services can be offered to the user by a set of logical CN nodes. The services offered by each logical CN node can be reconfigured in a relatively straightforward manner. Furthermore, it is relatively easy to add additional CN nodes to introduce new services.

The network of figure 2 includes a mobile station 20, base stations 21 and RNCs 22. The interconnection of these units and the general aspects of their operation are suitably as for the UMTS system of figure 1.

The network of figure 2 also includes a plurality of core network entities 23 any of which may communicate with any of the RNCs 22 via a distributed communication arrangement 24. The core networks 23 can communicate with external telecommunications networks 25 such as other mobile networks, the internet and fixed line networks, depending on the capabilities of the respective core network. For

example, a core network may include a mobile switching centre (MSC) 26 for communications via voice or fax protocols or a serving GPRS (general packet radio service) support node (SGSN) 27 for data protocol communications. In a large network not all of the core networks 25 may be able to communicate with all of the RNCs 22, for geographical network configuration reasons.

The RNCs 22 include processing apparatus 28 for processing communications through the RNCs, handling control of the base stations 21 (e.g. controlling handovers), managing access of mobile stations into the system, managing mobility (e.g. location management or radio resource management) of mobile stations in the system between base stations, and other functions.

When a mobile station makes contact with the network it makes radio communication with a base station and thereby establishes an RRC (radio resource control) connection with the RNC to which that base station is connected. In the course of setting up that connection the UTRAN indicates to the mobile station the available CN nodes (domains) offering services within the service area controlled by the respective RNC. For each domain the UTRAN indicates to the MS the service(s) offered by that domain, together with an identifier for the domain, suitably a logical identifier such as a core network access number that may be used by the mobile station or other network entities to identify that core network in communications and allow routing to that network.

The MS is aware of which services it supports and for which of those services it requires a connection to the network. The MS can therefore select one or more appropriate CN domains for providing the required service(s). The MS attempts to connect to each selected domain so that it can be provided with a desired service from that domain.

For example, if the MS connects to the network requiring a circuit switched fax connection and a packet switched voice connection, the MS receives from the UTRAN a message indicating the available domains and the services offered/supported by each. The MS then selects one CN domain that is offering a fax service and one CN domain that is offering a packet switched service capable of carrying voice traffic. The MS then attempts to make a connection to each one of those domains. The domains may be the same or different.

The process is illustrated generally in figure 3.

The said core network access number can simply be an identifier that is generated by the RNC for use in its communications with the MS. The MS can use the core network access number to indicate to the RNC which core network it wishes to access but the subsequent forwarding of an access request message on to the relevant core network may be done by the RNC using a different, true identifier that is unknown to the MS. Thus, from the point of view of the MS the RNC transparently passes its communications on to the relevant core network. Once a core network accepts and establishes an attachment to an MS the MS can be informed of a true identifier for the core network to allow it to direct communications to the core network via another RNC if necessary. The RNC preferably has logic to allow it to direct communications to a suitable CN serving entity of the desired domain – for example randomly, on the basis of information determined by the RNC, on the basis of information given to the RNC by one or more of the serving node (e.g. their loads) or on the basis of information given to the RNC by the user equipment (UE) (e.g. the identity of the entity that previously handled the UE's communications and therefore may have some information on the UE). When such an entity has been selected the RNC may address that entity by the identifier of a specific entity given to the user equipment by the entity itself.

As the mobile station moves within the network the base station(s) and the RNC(s) serving it may change, as may the serving nodes in the core network. To cope with this the UMTS system provides for mobility management (MM) protocol instances which handle location updates within the network in idle mode. In connected mode (i.e. when an RRC connection exists between the mobile station and an RNC) handover procedures are used, in which a connection is switched from a former node to a new node; the same principle is used whether the changing node is the BS, RNC or serving CN. In the system of figure 2, on attaching to a domain a mobile station initiates a UMTS mobility management instance especially for that domain. Therefore, associated with each MS there is a MM instance for each CN domain to which that MS is attached. In principle each MM instance operates independently of the others, following the UTRAN paging area indication and making appropriate location updates to its respective CN domain. (In practice the MM instances may be somewhat linked by, for example, a common paging area). By this means, each CN domain to which the MS is attached can be kept independently updated of the mobile station's location so that it can route communications to the mobile station accordingly.

As the operator updates the network and offers different services through different CN domains this is handled automatically through by the connection arrangement described above. When the MS accesses the network, if the operator now offers a service through a different CN node than before the MS simply attaches to the new CN node that is indicated to the mobile as being capable of providing the desired service. Thus the above arrangement copes automatically with the addition of new CN domains to provide services and with adjustment of the functional split of services between CN domains.

The system is preferably also capable of accommodating changes in the attachment pattern of the MS even whilst it is connected to the network. If the mobile receives from the UTRAN a message indicating a change in the split of services between CN

nodes that affects the services for which the mobile station is attached then it suitably changes its pattern of attachment to meet with the new split of services. To meet the new split of service any of the following changes may be made, as appropriate:

1. Changing the arrangement for provision of a service from one CN domain to which the MS is already attached to another CN domain to which the MS is already attached. In this case the existing MM instance for that CN domain can also be updated to reflect the change in services being accessed through the respective CN domain.
2. Dropping the attachment for provision of a service from one CN domain and establishing an attachment for provision of that service from another CN domain to which the MS was not previously attached. In this case the existing MM instance for the dropped CN domain can be terminated and a new MM instance established for the newly attached CN domain.

This capability offers great flexibility to operators in the provision of new services or the reconfiguration of a network to provide existing services through new nodes. In particular, as services migrate from the CS domain to the PS domain the above arrangement provides the capacity for relatively straightforward reconfiguration of MS to CN connections from nodes that formerly provided a service in the CS domain to nodes that provide an equivalent service in the PS domain.

If the mobile station is informed of the availability of a service that is unknown to the mobile station then it can suitably ignore the availability of that service. By this means the system described above may be used to assist in version management – that is to assist compatibility between older and newer equipment in the system. Thus older mobile stations that are not compatible with newer services can cope with indications of the availability of services with which they are not compatible.

The applicant draws attention to the fact that the present invention may include any feature or combination of features disclosed herein either implicitly or explicitly or any generalisation thereof, without limitation to the scope of any of the present claims. In



view of the foregoing description it will be evident to a person skilled in the art that various modifications may be made within the scope of the invention.

2000050 542600

**CLAIMS**

1. A method of establishing a connection in a telecommunications system in which an intermediate network provides for communications between a user terminal and one or more of a plurality of serving network entities each capable of providing communications services to the user terminal by means of at least one telecommunications protocol, the method comprising the step of the intermediate network transmitting to the user terminal an indication of the serving network entities and the communications services provided by each one.
2. A method as claimed in claim 1, wherein in order to receive a desired set of services the mobile station determines a set of the serving network entities indicated as together providing that set of services and attempts to establish a connection with the serving network entities in the set via the intermediate network.
3. A method as claimed in claim 2, wherein the said indication is generated by the intermediate network.
4. A method as claimed in any preceding claim wherein the user terminal is capable of communicating by radio with the intermediate network.
5. A method as claimed in any preceding claim wherein the intermediate network is operable according to the Universal Mobile Telecommunications System or a derivative thereof.
6. A method as claimed in claim 5, wherein the serving network entities are core networks.
7. A method as claimed in any preceding claim, wherein the intermediate network is a radio access network.

8. A method as claimed in claim 7, wherein the intermediate network is a Universal Mobile Telecommunications System radio access network.
9. A method as claimed in any preceding claim, wherein the said indication is transmitted to the user terminal during the establishment of a connection between the user terminal and the intermediate network.
10. A method as claimed in any preceding claim, wherein the said indication is transmitted to the user terminal during establishment of a radio resource control connection between the user terminal and the intermediate network.
11. A method as claimed in any of claims 1 to 8, wherein said indication is transmitted to the user after establishment by the of a connection between the user terminal and the intermediate network.
12. A method as claimed in any of claims 1 to 8 or 11, wherein the said indication is transmitted to the user terminal during a procedure of the intermediate network consequent on reallocation of equipment in the intermediate network serving the connection with the user terminal.
13. A method as claimed in claim 11 as dependant directly or indirectly on claim 5, wherein the said indication is transmitted to the user terminal in consequence of a serving radio network controller relocation.
14. A method as claimed in any preceding claim, wherein the said indication is transmitted to the user terminal in consequence of a change in serving network entity.

15. A method as claimed in any preceding claim, wherein the intermediate network is capable of adjusting the number of paging areas according to the number of serving network entities.
16. A method as claimed in any preceding claim, wherein at least one of the serving network entities is capable of providing for communications between the terminal and another telecommunications network.
17. A method as claimed in any preceding claim, wherein at least one of the serving network entities is capable of providing for circuit switched communications between the terminal and another telecommunications network.
18. A method as claimed in any preceding claim, wherein at least one of the serving network entities is capable of providing for packet switched communications between the terminal and another telecommunications network.
19. A method as claimed in any preceding claim, wherein the intermediate network is capable of routing signals between the user terminal and one of the serving network entities.
20. A method as claimed in claim 19, wherein the intermediate network is capable of routing signals from the mobile station to a selected one of the serving network entities on the basis of a core network domain indicator.
21. A method as claimed in claim 19 or 20, wherein the intermediate network includes a Universal Mobile Telecommunications System radio network controller capable of performing the said routing.
22. A method as claimed in any preceding claim, comprising establishing for each user terminal for each serving network entity with which that terminal is registered an

instance of a management process for informing the respective serving network of changes in the connection path to the respective mobile station through the intermediate network, whereby on a change in the connection path to the mobile station through the intermediate network, each serving network entity may be informed of the change by means of the respective instance.

23. A method as claimed in claim 22, comprising the step of, in consequence of the said indication of serving network entities and the communications services provided by each one, establishing a further instance of the management process for informing a respective serving network entity of changes in the connection path to the mobile station through the intermediate network.

24. A method as claimed in claim 22, comprising the step of, in consequence of the said indication of serving network entities and the communications services provided by each one, terminating an instance of the management process for informing a respective serving network entity of changes in the connection path to the said mobile station through the intermediate network.

25. A method as claimed in claim 23 or 24, comprising the step of, in consequence of the said indication of serving network entities and the communications services provided by each one, modifying an instance of the management process for informing a respective serving network entity of changes in the connection path to the said mobile station through the intermediate network.

26. A method as claimed in any of claims 22 to 25, wherein the management process is a mobility management process.

27. A method as claimed in claim 26, wherein the management process is operable in accordance with a mobility management protocol.

28. A telecommunications system comprising:

a user terminal;

one or more serving network entities each capable of providing communications services to the user terminal by means of at least one respective telecommunications protocol;

an intermediate network providing for communications between a user terminal and one or more of the serving network entities, and being capable of transmitting to the user terminal an indication of the serving network entities and the communications services provided by each one.

29. A telecommunications system as claimed in claim 28, comprising processing apparatus capable of for each user terminal establishing for each serving network entity with which that terminal is registered an instance of a management process for informing the respective serving network of changes in the connection path to the respective user terminal through the intermediate network, whereby on a change in the connection path to the user terminal through the intermediate network, each serving network entity may be informed of the change by means of the respective instance.

30. A method for establishing a connection substantially as herein described with reference to figures 2 and 3 of the accompanying drawings.

31. A method for managing communications substantially as herein described with reference to figures 2 and 3 of the accompanying drawings.

32. A telecommunications system substantially as herein described with reference to figures 2 and 3 of the accompanying drawings.

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
11 January 2001 (11.01.2001)

PCT

(10) International Publication Number  
WO 01/03454 A1

(51) International Patent Classification?: H04Q 7/24

(21) International Application Number: PCT/IB00/00989

(22) International Filing Date: 30 June 2000 (30.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
9915301.7 30 June 1999 (30.06.1999) GB

(71) Applicant (for all designated States except US): NOKIA  
NETWORKS OY [FI/FI]; Keilalahdentie 4, FIN-02150  
Espoo (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): AHMAVAARA, Kalle  
[FI/FI]; Nokia Networks Oy, Keilalahdentie 4, FIN-02150  
Espoo (FI).

(74) Agents: SLINGSBY, Philip, Roy et al.; Page White &  
Farrer, 54 Doughty Street, London WC1N 2LS (GB).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,  
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ,  
DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR,  
HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR,  
LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO,  
NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR,  
TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,  
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian  
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European  
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,  
IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG,  
CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— With international search report

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette



(54) Title: SERVICE MANAGEMENT



(57) Abstract: A method of establishing a connection in a telecommunications system in which an intermediate network provides for communications between a user terminal and one or more of a plurality of serving network entities each capable of providing communications services to the user terminal by means of at least one telecommunications protocol, the method comprising the step of the intermediate network transmitting to the user terminal an indication of the serving network entities and the communications services provided by each one.

WO 01/03454 A1

1/2





2/2




FIG. 3

**COMBINED DECLARATION AND POWER OF ATTORNEY****915-418**  
(Docket Number)

As a below named inventor, I hereby declare that:

- my residence, post office address and citizenship are as stated below next to my name;
- I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled: **SERVICE MANAGEMENT**,
- the specification of which is attached hereto unless the following box is checked: ☒. If the box is checked,  
the application was filed on **June 30, 2000**  
as U.S. Application Number  
or PCT International Application Number **PCT/IB00/00989**  
and was amended on (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR §1.56.

I hereby claim foreign priority benefits under 35 U.S.C. §119(a)-(d) or §365(b) of any foreign application(s) for patent or inventor's certificate, or §365(a) of any PCT International application which designated at least one country other than the United States, listed below and have also identified below, by checking the box, any foreign application for patent or inventor's certificate, or PCT International application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application			Priority Not Claimed
<b>GB 99/5301-7</b> (Application Number)	<b>GB</b> (Country)	<b>30 June 1999</b> (Day/Month/Year Filed)	<input type="checkbox"/>
(Application Number)	(Country)	(Day/Month/Year Filed)	<input type="checkbox"/>

To the extent permitted by rule or law, I hereby incorporate by reference the Prior Foreign Application(s) listed above.

I hereby claim the benefits under 35 U.S.C. §119(e) of any United States provisional application(s) listed below:

(Provisional Application Number)	(Day/Month/Year Filed)
(Provisional Application Number)	(Day/Month/Year Filed)

I hereby claim the benefit under 35 U.S.C. §120 of any United States application(s), or §365(c) of any PCT International application designating the United States, listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States or PCT International application in the manner provided by the first paragraph of 35 U.S.C. §112, I acknowledge the duty to disclose information which is material to patentability, as defined in 37 CFR §1.56, which became available between the filing date of the prior application and the national or PCT International filing date of this application.


(Application Number)	(Day/Month/Year Filed)	(Status--patented, pending, abandoned)
(Application Number)	(Day/Month/Year Filed)	(Status--patented, pending, abandoned)

The undersigned hereby authorizes the U.S. firm of Ware, Fressola, Van Der Sluys & Adolphson LLP to accept and follow instructions from the English firm of Page White & Farrer as to any action to be taken in the U.S. Patent and Trademark Office regarding this application, without direct communication between the U.S. firm and the undersigned. In the event of a change in the persons from whom instructions may be taken, the U.S. firm will be so notified by the undersigned or his successors and assigns.

I hereby appoint the attorney(s) and/or agent(s) assigned to the customer number listed below, as may from time to time be amended, belonging to the U.S. firm of Ware, Fressola, Van Der Sluys & Adolphson LLP, to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Customer Number


4955




Address all telephone calls to: Ware, Fressola, Van Der Sluys & Adolphson LLP at (203) 261-1234. Address all correspondence to:

Customer Number

4955



I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

<b>Kalle AHMAVAARA</b> Full name of sole or first inventor (given name, middle initial, FAMILY NAME(S) IN UPPER CASE)		
<input checked="" type="checkbox"/>  Inventor's Signature	<input checked="" type="checkbox"/> 13.03.2002 Date	
Espoo, Finland Residence	FI X	Finland Citizenship
Post Office Address: Merivirta 6 A 16, FIN-02320 Espoo, Finland		

Full name of second inventor (given name, middle initial, FAMILY NAME(S) IN UPPER CASE)		
_____ Inventor's Signature	_____ Date	
_____ Residence	_____ Citizenship	
Post Office Address:		

Full name of third inventor (given name, middle initial, FAMILY NAME(S) IN UPPER CASE)		
_____ Inventor's Signature	_____ Date	
_____ Residence	_____ Citizenship	